

# Product Information



## JOSCHU PICA HP 15

Acid Shade Remover

### General Information:

JOSCHU PICA HP 15 is a liquid, highly acid and rapidly effective shade remover. The highly pore permeable texture enables a very good removal of colour shades, also in deeper pores.

### Application:

JOSCHU PICA HP 15 is suitable for priming surfaces (e.g. concrete, bricks). Please apply with caution on the following surfaces: marble, lime stone, sandstone, as well as on other lime-/calcium-based surfaces.

### Processing:

Apply undiluted cleaner with a brush. The application should be effected bottom-up. Please moisturise the area below the graffiti with water before applying the cleaner. After the application incorporate the cleaner into the displaceable colour by using a brush or vylene pad. When the colour is dissolved, residence time approximately 5 – 10 minutes depending on the surface and the displaceable colour, remove the colour with hot water and pressure, or with warm water and cotton cloth respectively. Notice: A significantly longer residence time might be necessary with cold or wet weather conditions. Finally thoroughly neutralise the surface with water. However, please consider that the facade colour might be affected.

### Consumption:

Depending on the level of staining and the structure of the surface 0.2-0.4 l/m<sup>2</sup>, the exact consumption depends upon the surface / apply on trial area.

### Advice:

Generally check compatibility before usage. Please implicitly follow the application and security advice on the EC security data sheets.

### Marking:

Corrosive. Signalise as hazardous good on land carriage.  
UN 3265, ADR/RID Category 8



### Technical data:

Shelf life: 12 months from manufacturer date in original container  
Storage conditions: frost-protected, dry, dark and cool  
pH value: 1  
Article number: 61000/05 (5 litre container), 61000/25 (25 litre container)  
Biodegradable.

Product specific and security relevant advice is to be learned from the EC security data sheets.

Updated: 01.01.2011

The product information sheet serves for mere guidance. PICA KEMI AB does not assume any responsibility for the result. In case of uncertainty we recommend to contact the manufacturer or to conduct test pieces on a limited area.

Notice: The indications provided in this information sheet are affected based on our experiences to the best knowledge; however, they are non-binding. They are to be adapted to each individual construction site, designated use and the specific on-site demands. Under these preconditions, we are liable for the correctness in line with our sale and delivery conditions. Recommendations made by our employees that deviate from our information sheets are binding for us when they are confirmed in written form. In this case the acknowledged regulations of the technology are to be adhered to. Integral parts of the contract are our standard business conditions.

Version: 1/2011. This publication has been technically revised. Previous versions are invalid and are not allowed to be employed. With the publication of technically revised new editions this version becomes invalid. We reserve our right to modify the indicated data without announcement.

A3 Oberflächensysteme GmbH, Mainzer Straße 8, 56410 Montabaur



### Contact in Germany:

A3 Oberflächensysteme GmbH, Mainzer Straße 8  
56410 Montabaur  
Telefon: 026 02 – 106 08 06  
Telefax: 026 02 – 106 88 68  
E-Mail: Post@GraffitiSchutz.de  
Internet: www.GraffitiSchutz.de

